AIR/10NL



IT IMPIEGO

Tubo in gomma long length idoneo per mandata di acqua, fluidi inerti e aria.

- **TEMPERATURA:** -30°C +80°C

STRUTTURA

- **Sottostrato**: liscio in gomma nera SBR.
- **Rinforzi**: inserzioni di filati sintetici ad alta resistenza.
- **Copertura**: in gomma nera SBR/EPDM resistente all'abrasione ed agli agenti atmosferici.
- **Superficie**: liscia estrusa.
- **Marcatura**: ad inchiostro "H.T. - AIR/WATER - W.P. 10 BAR (150 PSI) - ISO R 1307".

Disponibile su richiesta
AIR10NL/ZINC: con trecciatura in acciaio zincato.
AIR10NL/INOX: con trecciatura in acciaio inox AISI 304 o 316.

EN APPLICATION

Long length rubber hose suitable for delivery of water, non corrosive fluids and air.

- **TEMPERATURE RANGE:** -30°C +80°C

CONSTRUCTION

- **Tube**: black, smooth SBR rubber.
- **Reinforcement**: high strength synthetic textile yarn.
- **Cover**: black, abrasion and weathering resistant SBR/EPDM rubber.
- **Surface**: smooth extruded.
- **Branding**: ink marking "H.T. - AIR/WATER - W.P. 10 BAR (150 PSI) - ISO R 1307"

Available on request:
AIR10NL/ZINC: galvanized braided.
AIR10NL/INOX: AISI 304 or 316 stainless braided.

DIAMETRO INTERNO INSIDE DIAMETER		DIAMETRO ESTERNO OUTSIDE DIAMETER		PESO TEORICO WEIGHT		PRESSIONE ESERCIZIO WORKING PRESSURE		PRESSIONE SCOPPIO BURST PRESSURE		RAGGIO DI CURVATURA BENDING RADIUS		LUNGHEZZA LENGTH	
mm	inch	mm	inch	kg/mt	lbs/ft	bar	psi	bar	psi	mm	inch	mt	ft
8	5/16"	15	19/32"	0.18	0.12	10	150	30	450	65	2.56"	100	328
10	3/8"	17	21/32"	0.21	0.14	10	150	30	450	80	3.15"	100	328
12	15/32"	18	23/32"	0.20	0.13	10	150	30	450	95	3.74"	100	328
13	1/2"	19	3/4"	0.22	0.15	10	150	30	450	105	4.13"	100	328
15	19/32"	21	27/32"	0.25	0.17	10	150	30	450	120	4.72"	100	328
16	5/8"	23	29/32"	0.31	0.21	10	150	30	450	130	5.12"	80	262
19	3/4"	26	1.1/32"	0.38	0.25	10	150	30	450	150	5.91"	50	164
20	25/32"	30	1.3/16"	0.57	0.38	10	150	30	450	160	6.30"	50	164
22	7/8"	30	1.3/16"	0.48	0.32	10	150	30	450	175	6.89"	50	164
25	1"	33	1.5/16"	0.56	0.37	10	150	30	450	200	7.87"	50	164
25	1"	35	1.3/8"	0.69	0.46	10	150	30	450	175	6.89"	50	164

Altri diametri e/o pressioni realizzabili su richiesta - Le caratteristiche e i dati tecnici possono essere modificati senza preavviso.

Other diameters and/or pressures are feasible upon request - The characteristics and technical data could be changed without warning.