# ALIMPOMP/PRESS/TR

PHTHALATE FREE

## IT IMPIEGO

**Tubo in pvc spiralato retinato alimentare** idoneo per aspirazione e mandata di fluidi in genere.

*Normative di riferimento:* **REG (EU) 10/2011 CL. A-B-C-D1.**

- **TEMPERATURA:** -5°C +65°C

## STRUTTURA

- **Sottostrato**: liscio in pvc trasparente.
- **Rinforzi**: spirale metallica incorporata con tessuti sintetici ad alta resistenza.
- **Copertura**: trasparente resistente all'abrasione, agli olii, ai carburanti e agli agenti atmosferici.
- **Superficie**: liscia.
- **Marcatura**: ALIMPOMP PRESS FOOD QUALITY - I.D. - REG (EU) 10/2011 CL A-B-C-$D_1$ - PHTHALATE FREE - Italy lotto.

**Disponibile su richiesta**: versione oil.

## EN APPLICATION

**Food quality Pvc hose** suitable for suction and delivery.

*Standards:* **REG (EU) 10/2011 CL. A-B-C-D1.**

- **TEMPERATURE RANGE** -5°C +65°C

## CONSTRUCTION

- **Tube**: transparent smooth PVC .
- **Reinforcement**: steel wire helix with high strength synthetic textile plies.
- **Cover**: abrasion, oils, fuels and weathering resistant PVC.
- **Surface**: smooth.
- **Branding**: ALIMPOMP PRESS FOOD QUALITY - I.D. - REG (EU) 10/2011 CL A-B-C-$D_1$ - PHTHALATE FREE - Italy lotto.

**Available on request**: oil version.

| DIAMETRO INTERNO INSIDE DIAMETER | | DIAMETRO ESTERNO OUTSIDE DIAMETER | | PESO TEORICO WEIGHT | | PRESS. ESERCIZIO WORKING PRESSURE | | PRESS.SCOPPIO BURST PRESSURE | | ASPIRAZ. VACUUM | RAGGIO CURVATURA BENDING RADIUS | | LUNGHEZZA LENGTH | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| mm | inch | mm | inch | kg/mt | lbs/ft | bar | psi | bar | psi | bar | mm | inch | mt | ft |
| 19 | 3/4" | 29 | 1. 5/32" | 0.42 | 0.28 | 20 | 300 | 60 | 900 | 0.9 | 85 | 3.34 | 60 | 196.80 |
| 25 | 1" | 36 | 1.13/32" | 0.67 | 0.44 | 20 | 300 | 60 | 900 | 0.9 | 90 | 3.54 | 60 | 196.80 |
| 32 | 1.1/4" | 43 | 1.11/16" | 0.80 | 0.53 | 16 | 240 | 48 | 720 | 0.9 | 110 | 4.33 | 60 | 196.80 |
| 35 | 1.3/8" | 47 | 1.3/4" | 1.05 | 0.55 | 14 | 210 | 42 | 630 | 0.9 | 120 | 4.72 | 60 | 196.80 |
| 40 | 1.1/2" | 52 | 2" | 1.10 | 0.70 | 14 | 210 | 42 | 630 | 0.9 | 130 | 5.12 | 30 | 100 |
| 45 | 1.3/4" | 58 | 2.1/4" | 1.40 | 0.93 | 14 | 210 | 42 | 630 | 0.9 | 155 | 6.10 | 30 | 100 |

Altri diametri e/o pressioni realizzabili su richiesta - Le caratteristiche e i dati tecnici possono essere modificati senza preavviso.

Other diameters and/or pressures are feasible upon request - The characteristics and technical data could be changed without warning.