ARIA COMPRESSA/25



IT IMPIEGO

Tubo in gomma cord idoneo per aria compressa per impieghi gravosi.

- **TEMPERATURA:** -30°C +80°C

STRUTTURA

- **Sottostrato**: liscio in gomma nera SBR resistente a tracce di olii nebulizzati.
- **Rinforzi**: tessuti sintetici ad alta resistenza.
- **Copertura**: in gomma nera SBR/EPDM resistente all'abrasione e agli agenti atmosferici.
- **Superficie**: liscia ad impressione tela.
- **Marcatura**: listino scritta bianca "H.T. - COMPRESSED AIR - W.P. 25 BAR (375 PSI)".

EN APPLICATION

Softwall rubber hose heavy duty air compressed delivery.

- **TEMPERATURE RANGE:** -30°C +80°C

CONSTRUCTION

- **Tube**: black, smooth SBR rubber oil mist resistant.
- **Reinforcement**: high strength synthetic textile plies.
- **Cover**: black, abrasion and weathering resistant SBR/EPDM rubber.
- **Surface**: smooth fabric finished.
- **Branding**: white transfer tape lettering "H.T. - COMPRESSED AIR - W.P. 25 BAR (375 PSI)".

DIAMETRO INTERNO INSIDE DIAMETER		DIAMETRO ESTERNO OUTSIDE DIAMETER		PESO TEORICO WEIGHT		PRESSIONE ESERCIZIO WORKING PRESSURE		PRESSIONE SCOPPIO BURST PRESSURE		LUNGHEZZA LENGTH	
mm	inch	mm	inch	kg/mt	lbs/ft	bar	psi	bar	psi	mt	ft
19	3/4"	32	1.1/4"	0.71	0.48	25	375	75	1125	40	131
25	1"	39	1.17/32"	0.94	0.63	25	375	75	1125	40	131
32	1.1/4"	48	1.7/8"	1.43	0.96	25	375	75	1125	40	131
38	1.1/2"	54	2.1/8"	1.65	1.11	25	375	75	1125	40	131
51	2"	69	2.23/32"	2.45	1.65	25	375	75	1125	40	131

Altri diametri e/o pressioni realizzabili su richiesta - Le caratteristiche e i dati tecnici possono essere modificati senza preavviso.

Other diameters and/or pressures are feasible upon request - The characteristics and technical data could be changed without warning.