CARBUPOMP/20NL



IT IMPIEGO

Tubo in gomma long length idoneo per adduzione di olii minerali, diesel e benzine ecologiche e HVO.

Compatibile con fluidi in accordo **EN 590:2010.**

- **TEMPERATURA:** -20°C +80°C

STRUTTURA

- **Sottostrato**: liscio in gomma nera NBR resistente ai prodotti petroliferi con contenuto aromatico non superiore al 50%.
- **Rinforzi**: inserzioni di filati sintetici ad alta resistenza.
- **Copertura**: in gomma nera nitrilica antistatica (R<1MΩ/m) resistente all'abrasione, ai carburanti, agli olii e agli agenti atmosferici.
- **Superficie**: liscia estrusa.
- **Marcatura**: ad inchiostro "H.T. - CARBUPOMP/20NL - W.P. 20 BAR - (R<1M Ω/m) - ISO R 1307".

Disponibile su richiesta:

CARBUPOMP/20NL/ZINC: con rivestimento in calza di acciaio zincato.

CARBUPOMP/20NL/INOX: con rivestimento in calza di acciaio inox.

EN APPLICATION

Long length rubber hose suitable for loading of mineral oils, diesel and unleaded fuel and HVO.

Compatible with fluids-according to **EN 590:2010.**

- **TEMPERATURE RANGE:** -20°C +80°C

CONSTRUCTION

- **Tube**: black, smooth, petroleum products up to 50% aromatic content resistant NBR rubber.
- **Reinforcement**: high strength synthetic textile yarn.
- **Cover**: black, abrasion, fuels, oils, and weathering resistant nitrilic antistatic rubber (R<1M Ω/m).
- **Surface**: smooth extruded.
- **Branding**: ink marking "H.T. - CARBUPOMP/20NL - W.P. 20 BAR - (R<1M Ω/m) - ISO R 1307".

Available on request:

CARBUPOMP/20NL/ZINC: galvanized steel wire braided cover.

CARBUPOMP/20NL/INOX: stainless wire braided cover.

DIAMETRO INTERNO INSIDE DIAMETER		DIAMETRO ESTERNO OUTSIDE DIAMETER		PESO TEORICO WEIGHT		PRESS. ESERCIZIO WORKING PRESSURE		PRESS. SCOPPIO BURST PRESSURE		LUNGHEZZA LENGTH	
mm	inch	mm	inch	kg/mt	lbs/ft	bar	psi	bar	psi	mt	ft
6	1/4"	13	1/2"	0,12	0,08	20	300	60	900	50	164
8	5/16"	16	5/8"	0,18	0,12	20	300	60	900	50	164
10	3/8"	18	3/4"	0,22	0,15	20	300	60	900	50	164
13	1/2"	21	7/8"	0,26	0,17	20	300	60	900	50	164
16	5/8"	24	23/32"	0,35	0,24	20	300	60	900	50	164
19	3/4"	29	1.5/32"	0.45	0.30	20	300	60	900	50	164
25	1"	35	1.3/8"	0.66	0.44	20	300	60	900	50	164

Altri diametri e/o pressioni realizzabili su richiesta - Le caratteristiche e i dati tecnici possono essere modificati senza preavviso.

Other diameters and/or pressures are feasible upon request - The characteristics and technical data could be changed without warning.