CEMENTUB/10



IT IMPIEGO

Tubo in gomma cord per mandata di cemento, sabbia umida e materiali abrasivi secchi.

- **TEMPERATURA:** -40°C +70°C

STRUTTURA

- **Sottostrato**: liscio in gomma nera NR/SBR antistatica resistente all'abrasione.
- **Rinforzi**: tessuti sintetici ad alta resistenza.
- **Copertura**: in gomma nera NR/SBR antistatica resistente all'abrasione e agli agenti atmosferici.
- **Superficie**: liscia ad impressione tela.
- **Marcatura**: listino scritta gialla "H.T. - CEMENTUB - TRUCK HOSE".

Disponibile su richiesta:
CEMENTUB/PA Sottostrato in gomma para beige.
CEMENTUB/SP10L con spirale in acciaio.
CEREALI/10 Sottostrato atossico bianco.

EN APPLICATION

Softwall bulk materials handling rubber hose suitable for delivery of cement, wet sand and dry abrasive materials.

- **TEMPERATURE RANGE:** -40°C +70°C

CONSTRUCTION

- **Tube**: black, smooth antistatic NR/SBR rubber abrasion resistant.
- **Reinforcement**: high strength synthetic textile plies.
- **Cover**: black, abrasion and weathering resistant antistatic NR/SBR rubber.
- **Surface**: smooth fabric finished.
- **Branding**: yellow transfer tape lettering "H.T. - CEMENTUB - TRUCK HOSE".

Available on request:
CEMENTUB/PA beige natural rubber Tube.
CEMENTUB/SP10L with steel wire.
CEREALI/10 white non toxic Tube.

DIAMETRO INTERNO INSIDE DIAMETER		DIAMETRO ESTERNO OUTSIDE DIAMETER		PESO TEORICO WEIGHT		PRESS. ESERCIZIO WORKING PRESSURE		PRESSIONE SCOPPIO BURST PRESSURE		LUNGHEZZA LENGTH	
mm	inch	mm	inch	kg/mt	lbs/ft	bar	psi	bar	psi	mt	ft
76	3"	90	3.9/32"	3.40	2.28	10	150	30	450	20/40	65.5/131
90	3.17/32"	106	4.3/16"	3.70	2.48	10	150	30	450	20/40	65.5/131
102	4"	110	4.5/16"	2.00	1.35	10	150	30	450	20	65.5
102	4"	118	4.5/8"	3.10	2.08	10	150	30	450	20	65.5

Altri diametri e/o pressioni realizzabili su richiesta - Le caratteristiche e i dati tecnici possono essere modificati senza preavviso.

Other diameters and/or pressures are feasible upon request - The characteristics and technical data could be changed without warning.