ESTINTORI/20NL

IT IMPIEGO

Tubo in gomma long length idoneo per passaggio di schiume e gas autoestinguenti a corredo di estintori.

• **TEMPERATURA:** -30°C +80°C

STRUTTURA

- **Sottostrato**: liscio in gomma nera EPDM.
- **Rinforzi**: inserzione di filati sintetici ad alta resistenza.
- **Copertura**: in gomma nera EPDM resistente agli agenti atmosferici e all'invecchiamento.
- **Superficie**: liscia estrusa.
- **Marcatura**: ad inchiostro "H.T. - FIRE EXTINGUISHER - HOSE TESTED 20 BAR".

EN APPLICATION

Long length rubber hose suitable or delivery of self-extinguishing foams and gases on extinguisher equipments.

• **TEMPERATURE RANGE:** -30°C +80°C

CONSTRUCTION

- **Tube**: black, smooth EPDM rubber.
- **Reinforcement**: high strength synthetic textile yarn.
- **Cover**: black, weathering and agents resistant EPDM rubber.
- **Surface**: smooth extruded.
- **Branding**: ink marking "H.T. - FIRE EXTINGUISHER - HOSE TESTED 20 BAR".

DIAMETRO INTERNO INSIDE DIAMETER		DIAMETRO ESTERNO OUTSIDE DIAMETER		PESO TEORICO WEIGHT		PRESSIONE ESERCIZIO WORKING PRESSURE		PRESSIONE SCOPPIO BURST PRESSURE		LUNGHEZZA LENGTH	
mm	inch	mm	inch	kg/mt	lbs/ft	bar	psi	mm	inch	mt	ft
10	3/8"	17	21/32"	0.22	0.14	20	300	60	900	100	328
10	3/8"	19	3/4	0.29	0.19	20	300	60	900	100	328
16	5/8"	26	1.1/32"	0.44	0.30	20	300	60	900	100	328
19	3/4"	29	1.5/32"	0.50	0.34	20	300	60	900	50	164

Altri diametri e/o pressioni realizzabili su richiesta - Le caratteristiche e i dati tecnici possono essere modificati senza preavviso.

Other diameters and/or pressures are feasible upon request - The characteristics and technical data could be changed without warning.