FOOD WATER/15BL-RL



GMP CE 2023/2006 · PHTALATE FREE · FDA

IT IMPIEGO

Tubo in gomma long length idoneo per mandata di acqua calda in impieghi dove sia richiesta alimentarità dei prodotti convogliati.

Normative di riferimento: **F.D.A.**

• **TEMPERATURA:** -35°C +120°C

STRUTTURA

- **Sottostrato**: liscio in gomma nera EPDM alimentare resistente al calore.
- **Rinforzi**: inserzioni di filati sintetici ad alta resistenza.
- **Copertura**: in gomma azzurra o rossa EPDM resistente all'abrasione, al calore e all'invecchiamento.
- **Superficie**: liscia estrusa.
- **Marcatura**: ad inchiostro "H.T. - FOOD QUALITY F.D.A. +120 °C".

EN APPLICATION

Long length rubber hose suitable for delivery of hot water where a food use hose is required.

Standards: **F.D.A.**

• **TEMPERATURE RANGE:** -35°C +120°C

CONSTRUCTION

- **Tube**: black, smooth, heat resistant food-quality EPDM rubber.
- **Reinforcement**: high strength synthetic textile yarn.
- **Cover**: blue or red, abrasion, heat and ageing resistant EPDM rubber.
- **Surface**: smooth extruded.
- **Branding**: ink marking "H.T. - FOOD QUALITY F.D.A. +120 °C".

DIAMETRO INTERNO INSIDE DIAMETER		DIAMETRO ESTERNO OUTSIDE DIAMETER		PESO TEORICO WEIGHT		PRESS. ESERCIZIO WORKING PRESSURE		PRESSIONE SCOPPIO BURST PRESSURE		LUNGHEZZA LENGTH	
mm	inch	mm	inch	kg/mt	lbs/ft	bar	psi	bar	psi	mt	ft
FOOD WATER/15BL											
11	7/16"	19	3/4"	0.26	0.17	15	225	45	675	100	328
13	1/2"	20	25/32"	0.27	0.18	15	225	45	675	100	328
FOOD WATER/15RL											
13	1/2"	20	25/32"	0.27	0.18	15	225	45	675	100	328

Altri diametri e/o pressioni realizzabili su richiesta - Le caratteristiche e i dati tecnici possono essere modificati senza preavviso.

Other diameters and/or pressures are feasible upon request - The characteristics and technical data could be changed without warning.