INTOTUB/40



ISO
DIN 4649

IT IMPIEGO

Tubo in gomma cord per lancio di betoncino, intonaco e gesso.

Normative di rispondenza: secondo **ISO DIN 4649 : max 50 mm³ ± 5.**

• **TEMPERATURA:** -40°C +70°C

STRUTTURA

- **Sottostrato**: liscio in gomma nera NR/SBR antistatica resistente all'abrasione.
- **Rinforzi**: tessuti sintetici ad alta resistenza.
- **Copertura**: in gomma nera NR/SBR antistatica resistente all'abrasione e agli agenti atmosferici.
- **Superficie**: liscia ad impressione tela.
- **Marcatura**: listino scritta arancione "H.T. - INTOTUB - PLASTER & CONCRETE DELIVERY - W.P. 40 BAR".

Disponibile su richiesta:
INTOTUB/40/W con copertura bianca.

EN APPLICATION

Softwall rubber hose engineered for plaster and concrete spraying**.**

Specifications: according to **ISO DIN 4649: max 50 mm³ ± 5.**

• **TEMPERATURE RANGE:** -40°C +70°C

CONSTRUCTION

- **Tube**: black, smooth antistatic NR/SBR rubber abrasion resistant.
- **Reinforcement**: high strength synthetic textile plies.
- **Cover**: black, abrasion and weathering resistant antistatic NR/SBR rubber.
- **Surface**: smooth fabric finished.
- **Branding**: orange transfer tape lettering "H.T. - INTOTUB - PLASTER & CONCRETE DELIVERY - W.P. 40 BAR".

Available on request:
INTOTUB/40/W with white cover.

DIAMETRO INTERNO INSIDE DIAMETER		DIAMETRO ESTERNO OUTSIDE DIAMETER		PESO TEORICO WEIGHT		PRESS. ESERCIZIO WORKING PRESSURE		PRESSIONE SCOPPIO BURST PRESSURE		LUNGHEZZA LENGTH	
mm	inch	mm	inch	kg/mt	lbs/ft	bar	psi	bar	psi	mt	ft
25	1"	38	1.1/2"	0.72	0.48	40	600	120	1800	60	196,5
32	1.1/4"	46	1.3/16"	0.94	0.63	40	600	120	1800	40	131
35	1.3/8"	49	1.15/16"	1.02	0.69	40	600	120	1800	40	131
40	1.9/16"	54	2.1/8"	1.08	0.73	40	600	120	1800	40	131
51	2"	67	2.41/64"	1.65	1.11	40	600	120	1800	40	131

Altri diametri e/o pressioni realizzabili su richiesta - Le caratteristiche e i dati tecnici possono essere modificati senza preavviso.

Other diameters and/or pressures are feasible upon request - The characteristics and technical data could be changed without warning.