# SABBIA/SP6C/PA




## IT IMPIEGO

**Tubo in gomma spiralato ondulato** idoneo per aspirazione e mandata in impieghi gravosi di sabbia, vetro, ceramica o graniglia metallica.

- **TEMPERATURA:** -40°C +70°C

## STRUTTURA

- **Sottostrato**: liscio in para beige resistente all'abrasione
- **Rinforzi**: tessuti sintetici ad alta resistenza, spirale metallica e cordicella di rame.
- **Copertura**: in gomma nera NR/SBR resistente all'abrasione e agli agenti atmosferici.
- **Superficie**: ondulata.
- **Marcatura**: listino arancio scritta nera "H.T. - BULK MATERIAL - S/D".

## EN APPLICATION

Long lasting heavy duty **hardwall corrugated Cover rubber hose** suitable for suction and delivery of sand, glass, ceramics and cast steel shot.

- **TEMPERATURE RANGE:** -40°C +70°C

## CONSTRUCTION

- **Tube**: beige, smooth, abrasion resistant para rubber.
- **Reinforcement**: high strength synthetic textile plies, helix wire and copper wire.
- **Cover**: black, abrasion and weathering resistant antistatic NR/SBR rubber.
- **Surface**: corrugated fabric finished.
- **Branding**: orange transfer tape black lettering "H.T. - BULK MATERIAL - S/D".

| DIAMETRO INTERNO INSIDE DIAMETER | | PESO TEORICO WEIGHT | | PRESS. ESERCIZIO WORKING PRESSURE | | PRESSIONE SCOPPIO BURST PRESSURE | | ASPIRAZ. VACUUM | RAGGIO CURVATURA BENDING RADIUS | | LUNGHEZZA LENGTH | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| mm | inch | kg/mt | lbs/ft | bar | psi | bar | psi | bar | mm | inch | mt | ft |
| 51 | 2" | 1,35 | 0,91 | 6 | 90 | 18 | 270 | 0,9 | 75 | 2,95 | 20/40 | 65.5/131 |
| 76 | 3" | 2,00 | 1.35" | 6 | 90 | 18 | 270 | 0,9 | 110 | 4.33" | 20/40 | 65.5/131 |
| 102 | 4" | 3,20 | 2.16" | 6 | 90 | 18 | 270 | 0,9 | 150 | 5.90" | 20/40 | 65.5/131 |
| 127 | 5" | 4,40 | 2,95 | 6 | 90 | 18 | 270 | 0,9 | 190 | 7.48" | 20 | 65.5 |
| 152 | 6" | 5,40 | 3,62 | 6 | 90 | 18 | 270 | 0,9 | 230 | 9.06" | 20 | 65.5 |

Altri diametri e/o pressioni realizzabili su richiesta - Le caratteristiche e i dati tecnici possono essere modificati senza preavviso.

Other diameters and/or pressures are feasible upon request - The characteristics and technical data could be changed without warning.