SAE J30 R9 - FKM



SAE J 30 R9

IT IMPIEGO

Tubo in gomma long length idoneo per adduzione di carburante diesel, BIODIESEL (B10, B20, B100), Benzina, E10 E15, E85 ed HVO.

Standards: **SAE J30 R9 .**

- **TEMPERATURA:** -25°C +135°C (picco -40°C +150°C)

STRUTTURA

- **Sottostrato**: liscio in gomma FKM (VYTON) per alte temperature, assenza di Zinco e Piombo.
- **Rinforzi**: inserzioni di filati Aramidici.
- **Copertura**: in gomma Eco nera speciale resistente agli oli, ai prodotti chimici, all'abrasione, al calore, all'ozono e all'invecchiamento.
- **Marcatura**: ad inchiostro "H.T. – PETROL/DIESEL/BIODIESEL – LOW PERMEABILITY – SAE J30 R9" - FKM - D.I. - R<1MΩ/m".

EN APPLICATION

Long length rubber hose suitable for fuel transfer systems Diesel, BIODIESEL (B10, B20, B100), Gas, E10, E15, E85, HVO.

Standards: **SAE J30 R9 .**

- **TEMPERATURE RANGE:** -25°C +135°C (peak -40°C +150°C)

CONSTRUCTION

- **Tube**: black, smooth, FKM (VITON) for high temperatures, Zinc and Lead free.
- **Reinforcement**: Textile Aramid.
- **Cover**: special black Eco rubber resistant to oils, chemicals, abrasion, heat, ozone, and ageing.
- **Branding**: : ink marking "H.T. – PETROL/DIESEL/BIODIESEL – LOW PERMEBILITY – SAEJ 30 R9" FKM - I.D. - R<1MΩ/m".

DIAMETRO INTERNO INSIDE DIAMETER		DIAMETRO ESTERNO OUTSIDE DIAMETER		PESO TEORICO WEIGHT		PRESS. ESERCIZIO WORKING PRESSURE		PRESS. SCOPPIO BURST PRESSURE		LUNGHEZZA LENGTH	
mm	inch	mm	inch	kg/mt	lbs/ft	bar	psi	bar	psi	mt	ft
6	1/4"	12,5	1/2"	0.14	0.10	10	150	62	930	>10	>32.8
8	5/16"	14.5	19/32"	0.18	0.12	10	150	62	930	>10	>32.8
10	3/8"	17,2	21/32"	0.21	0.14	10	150	34	510	>10	>32.8
13	1/2"	20,2	25/32"	0.26	0.17	10	150	34	510	>10	>32.8

Altri diametri e/o pressioni realizzabili su richiesta - Le caratteristiche e i dati tecnici possono essere modificati senza preavviso.

Other diameters and/or pressures are feasible upon request - The characteristics and technical data could be changed without warning.